

MAXSERIES



WORK IN COMFORT

Mahindra's own mComfort seat is built for maximum ergonomic support. Features include extra cushioning for operator comfort, air suspension seats, and foldable armrests.



HEAVIER OPERATING WEIGHT

At 1,715 to 1,973 lbs (varies by model), the Max series is heavier than other small compact vehicles in its class. Equipped with a sturdy, well-built steel mid-compact chassis, the Max series offers supreme stability.



EASY IMPLEMENT INSTALLATION

Designed for exceptional convenience and simplicity, users may install a backhoe, as well as an extensive range of attachments and implements, quickly and easily.

MAX SERIES ATTACHMENTS

| TRACTOR | MAX 25XL HST | MAX 26XLT HST | MAX 26XLT SHUTTLE |
|---|------------------|---------------|-------------------|
| LOADER MODEL | MXL25L | | MXLT26L |
| Standard Bucket Size [in] | 50 | | 54 |
| Maximum Lift Height [in] | 75 | | 82.7 |
| Dig Depth [in] | 4 | | 2.6 |
| Lift Capacity to Full Height at Pivot Pin [lbs] | 900 | | 1402 |
| Breakout Force [lbs] | 2000 | | 2690 |
| Shipping Weight [lbs] | 545 | | 627 |
| BACKHOE MODEL | | 26B | |
| Standard Bucket Size [in] | | 12 | |
| Maximum Dig Depth [in] | | 80 | |
| Dig Depth 2' Flat Bottom [in] | | 78.5 | |
| Dig Force Bucket [lbs] | | 2270 | |
| Dig Force Dipper [lbs] | | 1248 | |
| Shipping Weight [lbs] | | 610 | |
| MOWER MODEL | 62M | | 65M |
| Type | Side Discharge | | Side Discharge |
| Cutting Width [in] | 60 | | 60 |
| Cutting Height [in] | 1-4 | | 1-4 |
| Transport Height [in] | 5 | | 5 |
| Lift Linkage Type | Wrap Around Type | | Wrap Around Type |
| Height Adjustment | Dial Gauge | | Bushing Adjust |
| Number of Blades | 3 | | 3 |
| Blade Tip Speed [FPM] | 17350 | | 17350 |
| Weight [lbs] | 411 | | 411 |
| Adjustable Anti-Scalp Wheels | 4 | | Ground Following |

MAX SERIES SPECIFICATIONS

| TRACTOR | MAX 25 XL HST | MAX 26XLT HST | MAX 26XLT SHUTTLE |
|-------------------------------------|--|--|-------------------|
| ENGINE | | | |
| Type | Four-stroke, Naturally Aspirated, Indirect Injection, Water Cooled Diesel Engine | | |
| Engine HP (kW) @ RPM | 24 (17.9) @ 2500 | 25.9 (19.3) @ 2500 | |
| Displacement [in³ (cc)] | 80.4 (1318) | | |
| Number of Cylinders | 3 | | |
| Fuel Tank [gal (L)] | 6.1 (23) | | |
| DRIVE TRAIN | | | |
| Transmission | HST - 2 ranges | Synchromesh on Shuttle (Forward-Reverse Position) and main Gear Shift of constant mesh | |
| Number of Speeds | Infinite | 8F / 8R | |
| Clutch | Dry - Single | | |
| Brakes | Wet-Disc | | |
| PTO | | | |
| Type | Live | Trans | |
| Rear PTO RPM | 540 @ 2376 | | |
| Mid PTO RPM | 2000 (Std) @ 2556 | 2000 (Opt.) @ 2526 | |
| PTO HP (kW) | 20 (14.9) | 20.2 (15) | 21.7 (16.2) |
| HYDRAULICS | | | |
| Type | Open Center | | |
| Implement Pump Output [gpm (L/min)] | 4.6 (17.5) | 5.8 (22.1) | |
| Maximum Total Flow [gpm (L/min)] | 7.3 (27.6) | 8.5 (32.2) | |
| 3-Point Hitch | CAT I | | |
| Lift Capacity [lb (kg)] | 1354 (614) | 2315 (1050) | |
| ELECTRICAL | | | |
| Battery | 12 V, 450 CCA | | |
| Alternator | 12 V, 50 A | | |
| DIMENSIONS | | | |
| Overall Length [in (mm)] | 106.1 (2695) | 110 (2795) | |
| Overall Width [in (mm)] | 50.7 (1290) | 54.3 (1380) | |
| Overall Height [in (mm)] | 81.5 (2070) | 84.3 (2140) | |
| Wheelbase [in (mm)] | 58.2 (1480) | 63.2 (1605) | |
| Minimum Ground Clearance [in (mm)] | 7.2 (182) | 11.4 (290) | |
| Turning Radius [ft (m)] | 7.2 (2.2) | 7.2 (2.2) | |
| Weight [lb (kg)] | 1715 (778) | 1973 (895) | 1896 (860) |
| WHEELS & TIRES | | | |
| AG [Front/Rear] | 6 x 12 / 9.5 x 16 | 7-12 / 9.5-16 | |
| IND [Front/Rear] | 20 x 8-10 / 27 x 12.5-15 | 23 x 8.50-12 / 12-16.5 | |
| TURF [Front/Rear] | 20 x 8-10 / 29 x 12.5-15 | 23 x 8.5-12 / 33 x 12.5-15 | |